

Interior paint and varnish coating type AMERCOAT 391 PC									
Total:									
Total :									

Special conditions: special conditions:

- A. CARBON EQUIVALENT C_{eq} - NO MORE THAN 0.48 \\ Carbon equivalent SECB - Not more 0.48
- B . TEMPORARY RESISTANCE - NOT LESS than 440 N \ mm2 \\ Temporary resistance- Not less than 440 H\mm2
- C . LIMIT VOLUME - NOT LESS THAN 265H\mm2 \\ The yield strength is at least – 265 H\mm2
- D. RELATIVE EXTENSION - NOT LESS THAN 18% \\ Relative elongation-not less than 18%
- E . IMPACT VISCOSITY KCU (METAL) - NOT TESTED \\ KCU shock viscosity (metal) - not experienced
- F. IMPACT VISCOSITY KCU (WELDED CONNECTION) - NOT TESTED \\ KCU shock viscosity (welded) -not experienced
- G. PRESSURE HYDRO -TEST - 5.6 MPa (58 KGS \ CM 2) \\ Pressure of hydro-test - 5.6 MPa (58 kgf \ cm2)
- N . TIME EXPOSURE time -10 seconds _

Indicators for stamps steel 20 GOST 10704-91 \\ These are indicators for Steel 20 GOST 10704-91

All special requirements must be specified in the invoice and contract.

